Instruction for 5759 Lifter Retaining Clips

When disassembling the VW engine these valve lifter retaining clips can be used to keep the lifters from falling out of the bosses. Simply squeeze the retaining clip ends and insert them into the lifters through the holes in the case where the push rods came out. One spring clip will retain two lifters at once. Use the two clips on the four lifters of the case half you are lifting up. The other lifters will stay with the case half on the engine stand. When assembling an engine, do just the opposite using the retaining clips to keep the lifters from falling out when setting one case half on the other. When reusing lifters it is a good practice to place them in the same position they came out of.

99-4070-0/415

Instruction for 5759 Lifter Retaining Clips

When disassembling the VW engine these valve lifter retaining clips can be used to keep the lifters from falling out of the bosses. Simply squeeze the retaining clip ends and insert them into the lifters through the holes in the case where the push rods came out. One spring clip will retain two lifters at once. Use the two clips on the four lifters of the case half you are lifting up. The other lifters will stay with the case half on the engine stand. When assembling an engine, do just the opposite using the retaining clips to keep the lifters from falling out when setting one case half on the other. When reusing lifters it is a good practice to place them in the same position they came out of.

99-4070-0/415

Instruction for 5759 Lifter Retaining Clips

When disassembling the VW engine these valve lifter retaining clips can be used to keep the lifters from falling out of the bosses. Simply squeeze the retaining clip ends and insert them into the lifters through the holes in the case where the push rods came out. One spring clip will retain two lifters at once. Use the two clips on the four lifters of the case half you are lifting up. The other lifters will stay with the case half on the engine stand. When assembling an engine, do just the opposite using the retaining clips to keep the lifters from falling out when setting one case half on the other. When reusing lifters it is a good practice to place them in the same position they came out of.

99-4070-0/415

Instruction for 5759 Lifter Retaining Clips

When disassembling the VW engine these valve lifter retaining clips can be used to keep the lifters from falling out of the bosses. Simply squeeze the retaining clip ends and insert them into the lifters through the holes in the case where the push rods came out. One spring clip will retain two lifters at once. Use the two clips on the four lifters of the case half you are lifting up. The other lifters will stay with the case half on the engine stand. When assembling an engine, do just the opposite using the retaining clips to keep the lifters from falling out when setting one case half on the other. When reusing lifters it is a good practice to place them in the same position they came out of.

99-4070-0/415

Instruction for 5759 Lifter Retaining Clips

When disassembling the VW engine these valve lifter retaining clips can be used to keep the lifters from falling out of the bosses. Simply squeeze the retaining clip ends and insert them into the lifters through the holes in the case where the push rods came out. One spring clip will retain two lifters at once. Use the two clips on the four lifters of the case half you are lifting up. The other lifters will stay with the case half on the engine stand. When assembling an engine, do just the opposite using the retaining clips to keep the lifters from falling out when setting one case half on the other. When reusing lifters it is a good practice to place them in the same position they came out of.

99-4070-0/415

Instruction for 5759 Lifter Retaining Clips

When disassembling the VW engine these valve lifter retaining clips can be used to keep the lifters from falling out of the bosses. Simply squeeze the retaining clip ends and insert them into the lifters through the holes in the case where the push rods came out. One spring clip will retain two lifters at once. Use the two clips on the four lifters of the case half you are lifting up. The other lifters will stay with the case half on the engine stand. When assembling an engine, do just the opposite using the retaining clips to keep the lifters from falling out when setting one case half on the other. When reusing lifters it is a good practice to place them in the same position they came out of.

99-4070-0/415

Instruction for 5759 Lifter Retaining Clips

When disassembling the VW engine these valve lifter retaining clips can be used to keep the lifters from falling out of the bosses. Simply squeeze the retaining clip ends and insert them into the lifters through the holes in the case where the push rods came out. One spring clip will retain two lifters at once. Use the two clips on the four lifters of the case half you are lifting up. The other lifters will stay with the case half on the engine stand. When assembling an engine, do just the opposite using the retaining clips to keep the lifters from falling out when setting one case half on the other. When reusing lifters it is a good practice to place them in the same position they came out of.

99-4070-0/415

Instruction for 5759 Lifter Retaining Clips

When disassembling the VW engine these valve lifter retaining clips can be used to keep the lifters from falling out of the bosses. Simply squeeze the retaining clip ends and insert them into the lifters through the holes in the case where the push rods came out. One spring clip will retain two lifters at once. Use the two clips on the four lifters of the case half you are lifting up. The other lifters will stay with the case half on the engine stand. When assembling an engine, do just the opposite using the retaining clips to keep the lifters from falling out when setting one case half on the other. When reusing lifters it is a good practice to place them in the same position they came out of.

99-4070-0/415

Instruction for 5759 Lifter Retaining Clips

When disassembling the VW engine these valve lifter retaining clips can be used to keep the lifters from falling out of the bosses. Simply squeeze the retaining clip ends and insert them into the lifters through the holes in the case where the push rods came out. One spring clip will retain two lifters at once. Use the two clips on the four lifters of the case half you are lifting up. The other lifters will stay with the case half on the engine stand. When assembling an engine, do just the opposite using the retaining clips to keep the lifters from falling out when setting one case half on the other. When reusing lifters it is a good practice to place them in the same position they came out of.

99-4070-0/415