



Installation Instructions for Type 1 Two Piece Half Mask

Accessories enclosed: (4) wire hooks for hood section, (4) nuts and (2) vinyl-coated wires for body section.

Hood Section:

Open hood and secure. Position hood portion of mask over hood. Following diagram below; Take cord "A" attached to the mask and draw it back to point #1 (Hole in hood gusset closest to center back of hood). Place one wire hook in this hole and run cord thru it, keeping the cord tight, thread thru mask grommet flap #2 on opposite side. Place another wire hook in point #3, thread cord thru this hook and tie off as tightly as possible. Repeat sequence for the opposite side. Re-tighten the cords alternately until there is no slack remaining.

Body Section:

If car is a Super Beetle, remove washer bottle. Place body portion of mask over fenders and lower front apron. Place brass grommets in mask over fender studs that protrude into trunk and fasten into place with nuts provided. Using the vinyl-coated wire, start at the center bottom, hook the wire on the underside, then draw wire toward and thru the loop provided on the mask, pull tight, bend wire and twist. Starting at the center work up around fender by bending tabs provided, down and up under the fender flange. Repeat for opposite side. Work the material out with your hands and align headlight holes over the headlights. A slight hood latch adjustment may be necessary. This can be done by using a screwdriver on the bottom end of latch and unscrewing it one half turn while holding the nut above the spring in position.

IMPORTANT: DO NOT allow moisture to collect under the mask as it can cause a "Clouding" of the paint. If the underside of the mask becomes wet, remove the mask immediately and allow it and the car to dry before reinstalling. Maintain a wax finish under this mask at all times. Be sure finish is cured if car has been re-painted. Mask should be clean before storing or installation. **NOTE:** To aid in first time installation of the mask it is a good idea to fit it on a warm day. Prior to fitting lay out the mask in the sun so that the vinyl becomes more pliable. This will help you to correctly fit the mask to the contours of the vehicle. **WE WILL NOT BE RESPONSIBLE FOR ANY DAMAGE TO MASK OR CAR RESULTING FROM IMPROPER INSTALLATION/REMOVAL OF MASK.**

