



Installation of Karmann Ghia

Front portion of car should be free of dirt and dust.

1. Place cover on car so light openings match.
2. Bend tubs to fit wheel openings on stretch cords.
3. Bend remaining tabs and secure cover around bumper brackets with Velcro tape.
4. Insert plastic strips into (A Frame) stabilizers on top of cover. Four total.

- * Protect cover from dirt and dust, when not in use. Be sure cover is clean before storing and installing.
- * If underside of cover becomes wet, do not allow cover to dry on car. Heat from sun can cause clouding of paint. Cover and car must be dry when reinstalling.
- * The cover will be much easier to install if it is warm. Once installed the cover will after several hours, form to the car and thereafter be much easier to reinstall.

WE WILL NOT BE RESPONSIBLE FOR ANY DAMAGE TO CAR OR COVER FROM IMPROPER INSTALLATION OR REMOVAL OF COVER.

99-4143/0706



Installation of Karmann Ghia

Front portion of car should be free of dirt and dust.

1. Place cover on car so light openings match.
2. Bend tubs to fit wheel openings on stretch cords.
3. Bend remaining tabs and secure cover around bumper brackets with Velcro tape.
4. Insert plastic strips into (A Frame) stabilizers on top of cover. Four total.

- * Protect cover from dirt and dust, when not in use. Be sure cover is clean before storing and installing.
- * If underside of cover becomes wet, do not allow cover to dry on car. Heat from sun can cause clouding of paint. Cover and car must be dry when reinstalling.
- * The cover will be much easier to install if it is warm. Once installed the cover will after several hours, form to the car and thereafter be much easier to reinstall.

WE WILL NOT BE RESPONSIBLE FOR ANY DAMAGE TO CAR OR COVER FROM IMPROPER INSTALLATION OR REMOVAL OF COVER.

99-4143/0706



Installation of Karmann Ghia

Front portion of car should be free of dirt and dust.

1. Place cover on car so light openings match.
2. Bend tubs to fit wheel openings on stretch cords.
3. Bend remaining tabs and secure cover around bumper brackets with Velcro tape.
4. Insert plastic strips into (A Frame) stabilizers on top of cover. Four total.

- * Protect cover from dirt and dust, when not in use. Be sure cover is clean before storing and installing.
- * If underside of cover becomes wet, do not allow cover to dry on car. Heat from sun can cause clouding of paint. Cover and car must be dry when reinstalling.
- * The cover will be much easier to install if it is warm. Once installed the cover will after several hours, form to the car and thereafter be much easier to reinstall.

WE WILL NOT BE RESPONSIBLE FOR ANY DAMAGE TO CAR OR COVER FROM IMPROPER INSTALLATION OR REMOVAL OF COVER.

99-4143/0706



Installation of Karmann Ghia

Front portion of car should be free of dirt and dust.

1. Place cover on car so light openings match.
2. Bend tubs to fit wheel openings on stretch cords.
3. Bend remaining tabs and secure cover around bumper brackets with Velcro tape.
4. Insert plastic strips into (A Frame) stabilizers on top of cover. Four total.

- * Protect cover from dirt and dust, when not in use. Be sure cover is clean before storing and installing.
- * If underside of cover becomes wet, do not allow cover to dry on car. Heat from sun can cause clouding of paint. Cover and car must be dry when reinstalling.
- * The cover will be much easier to install if it is warm. Once installed the cover will after several hours, form to the car and thereafter be much easier to reinstall.

WE WILL NOT BE RESPONSIBLE FOR ANY DAMAGE TO CAR OR COVER FROM IMPROPER INSTALLATION OR REMOVAL OF COVER.

99-4143/0706